

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11) Publication number:

**0 559 109 A1**

(12)

## EUROPEAN PATENT APPLICATION

(21) Application number: **93103182.7**

(51) Int. Cl.<sup>5</sup>: **H01G 9/02, H01G 9/00,  
H01G 9/05**

(22) Date of filing: **27.02.93**

(30) Priority: **02.03.92 JP 44676/92**

(43) Date of publication of application:  
**08.09.93 Bulletin 93/36**

(84) Designated Contracting States:  
**DE FR GB**

(71) Applicant: **E.I. DU PONT DE NEMOURS AND  
COMPANY**  
**1007 Market Street**  
**Wilmington Delaware 19898(US)**

(72) Inventor: **Inaba, Akira**  
**3-22-5, 22-13-405 Kirigaoka, Midori-ku**  
**Yokohama-shi, Kanagawa-ken 227(JP)**

(74) Representative: **von Kreisler, Alek et al**  
**Patentanwälte von Kreisler-Selting-Werner,**  
**Postfach 10 22 41, Bahnhofsvorplatz 1**  
**D-50462 Köln (DE)**

(54) **Tantalum solid electrolytic capacitor.**

(57) To provide a tantalum solid electrolytic capacitor which enables to prevent a short-circuit due to diffusion of metals component contained in conductive polymer resin layer forming the cathode. A tantalum solid electrolytic capacitor comprising a fluorocarbon resin layer or a fluorocarbon resin containing layer being disposed between an anode composed of sintered tantalum having a surface of a dielectric oxide film and a cathode composition formed from a metal-containing conductive polymer resin composition, which may contain such fluorocarbon resin therein.

**EP 0 559 109 A1**